



气动陶瓷双闸板阀  
Pneumatic Ceramic Dual-plate Ceramic Valve

技术规范 Technical Specification

设计与制造 Design and Manufacture		GB/T12234
连接端尺寸 Connection End	结构长度 Face-to-face Dimension	厂商标准
	法兰尺寸 Flange End	GB/T9113 / ASME B16.5
检验与试验 Inspection & Test		JB/T9092
材料 Material	碳钢 Carbon steel	GB/T12229
	不锈钢 Stainless steel	GB/T12230
标志Mark		GB/T12220
供货Delivery		GB/T12252

主要部件材料 Material Specification

序号No.	名称Name	材料Material	序号No.	名称Name	材料Material
1	阀体 Body	WCB/CF8	9	组合填料环 Parking ring	PTFE
2	阀盖Bonnet	A105/SS304	10	螺柱Stud	A193-B7/B8
3	阀板座Plate seat	WCB/ CF8	11	螺母Nut	A194-2H/B8
4	阀板Plate	结构陶瓷Structural ceramic	12	弹簧Spring	16Mn
5	弹簧Spring	16Mn	13	气缸支架 Cylinder bracket	WCB/CF8
6	吊钩Hook	WCB/CF8	14	填料压环 Packing ring	45#
7	阀座Seat	结构陶瓷Structural ceramic	15	气动装置 Pneumatic actuator	组件 Components
8	阀杆Stem	2Cr13/SS304			

GB/T 9113

DN	L1	L2	PN10(1.0MPa)						
			D	D1	D2	b	f	N-M	Z-d
50	120	200	165	125	102	18	3	4-M16	4-Φ18
65	120	220	185	145	122	18	3	4-M16	4-Φ18
80	120	240	200	160	138	20	3	8-M16	8-Φ18
100	120	280	220	180	158	20	3	8-M16	8-Φ18
125	160	300	250	210	188	22	3	8-M16	8-Φ18
150	160	320	285	240	212	22	3	8-M20	8-Φ22
200	160	350	340	295	268	24	3	8-M20	8-Φ22
250	200	400	395	350	320	26	3	12-M20	12-Φ22
300	200	450	445	400	370	26	4	12-M20	12-Φ22

注：更多尺寸，请联系有氟密工程师。

Note: For more size, please consult our engineer.